

Respirator Type: Continuous Flow Supplied Air Respirator

Assigned Protection Factor: 1,000

Materials

Lens: Inner - .040" Tritan™, 54 square inches
EN 166 protection (low energy impact)

Outer – 0.40" Acetate, 66 square inches

Helmet: High Density Polyethylene

Shell: High Density Polyethylene

Breathing Tube: PVC with Coil Reinforcing

Cape: 28" length, Denier Nylon



Air Delivery: Air inlet situated at the back 5 o'clock position. Air inlet directs air across the inner shell air plenum directly to the user's breathing zone.

Suspension/Headgear: 88VXTG Adjustable Pinlock
88VXRT Adjustable Ratchet

Available Fittings: Adjustable 6 mm Industrial Interchange (steel) quick-disconnect nipple (1/4" NPT)

Lot Code Identification: Yes

Country of Origin: USA

Americas:
Bullard
1898 Safety Way
Cynthiana, KY 41031-9303 • USA
Toll-free within USA: 877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-234-8987

Europe:
Bullard GmbH
Lilienthalstrasse 12
53424 Remagen • Germany
Tel: +49-2642 999980
Fax: +49-2642 9999829

Asia-Pacific:
Bullard Asia Pacific Pte. Ltd.
LHK Building
701, Sims Drive, #04-03
Singapore 387383
Tel: +65-6745-0556
Fax: +65-6745-5176



©2017 Bullard. All rights reserved.